

TECHNICAL DATA SHEET GREASE: **HEAVY DUTY +**

Multi-service grease with extreme pressure additives, designed for intensive applications in heavy industry

Advantages :

- Excellent performance under very high loads, at high and low speed
- Suitable for ball and roller bearings
- Very good water resistance
- Excellent protection against wear and corrosion
- Good mechanical stability

Characteristics	Method	Unit	LUB HEAVY DUTY +
Temperature range			-30C / +150 °C
Colour			Blond
Texture			Smooth
Density	ISO 2811	g/cm ³	0,89
Worked penetration 60 strokes	ISO 2137	10 ⁻¹ mm	265/295
NLGI Grade	ISO 6743		2
Thickener type			Lithium
Base oil type			Mineral
Base oil viscosity at 40°C	ISO 3104	cSt	150
Base oil viscosity at 100°C	ISO 3104	cSt	15
Dropping point	ISO 2176	°C	190
Compatibility to thermoplastics	SNR Test		Ok
Compatibility to synthetic elastomers	SNR Test		Ok

*) : Speed factor: Speed in rotations / min X Average diameter of the bearing in mm

Typical applications:

Intensive applications in heavy industry: steel industry, construction, transport, etc.
Examples: Conveyors, lifting equipment, lorry wheel hubs, high power electric motor, water pumps, presses, etc.

Edition : 28/07/2011